

PATENT
930039-2039

IN THE CLAIMS

Please cancel claims 2-6.

Please amend claims 1 and 22 as follows:

5/13/02
1
B
--1(amended). A method for manufacturing a papermaker's fabric, said method comprising the steps of:

providing a laminated structure, said laminated structure having a bottom layer and a top layer, said bottom layer and said top layer each being strips of equivalent width and being laminated together, said bottom layer being transversely offset with respect to said top layer so that an unlaminated portion of said bottom layer is along one lateral edge of said laminated structure and an unlaminated portion of said top layer is along the other lateral edge of said laminated structure;

spirally winding said laminated structure in a plurality of turns wherein said unlaminated portion of said top layer in one turn of said laminated structure overlies said unlaminated portion of said bottom layer in an adjacent turn of said laminated structure; and

joining said overlying unlaminated portion of said top layer to said unlaminated portion of said bottom layer to form said papermaker's fabric, said joining including one or more operations (excepting) interlocking said overlying unlaminated

PATENT
930039-2039

B 1
portion with said top layer to said un laminated portion of said bottom layer and being selected from the group consisting of sewing, stitching, welding, needling, fusing and gluing said overlying un laminated portion with said top layer to said un laminated portion of said bottom layer, and said papermaker's fabric being in the form of an endless loop having an inner surface and an outer surface.--

B² --22(amended). A papermaker's fabric for a paper machine, said papermaker's fabric comprising:

B² a laminated structure, said laminated structure having a bottom layer and a top layer, said bottom layer and said top layer each being strips of equivalent width and being laminated together, said bottom layer being transversely offset with respect to said top layer, so that an un laminated portion of said bottom layer is along one lateral edge of said laminated structure and an un laminated portion of said top layer is along the other lateral edge of said laminated structure; said laminated structure being spirally wound in a plurality of turns wherein said un laminated portion of said top layer in one turn of said laminated structure overlies said un laminated portion of said bottom layer in an adjacent turn of said laminated structure; said overlying un laminated portion of said top layer being joined to said un laminated portion of said bottom layer by

not